## Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

## Listing of Claims:

- 1. (currently amended) A programmable unit, comprising:
- at least one program operation unit for running a program;
- a stopping device connected to said program operation unit, said stopping device stopping the running of the program by said program operation unit, said stopping device being located on the same chip as said program operation unit; and

other components connected to said stopping device, said stopping device also issuing a stop command causing said other components to be stopped, in addition to stopping said program operation unit with which said stopping device is associated; and

said other components including at least one further program operation unit or at least one peripheral, said stopping command being selectively provided from said stopping device to said other component if said other component is said further program operation unit and said stop command being

directly provided from said stopping device to said other component if said other component is a peripheral.

- 2. (currently amended) The programmable unit according to claim 1, wherein said other components include <u>said</u> at least one further program operation unit and said stopping device able to stop said further program operation unit which is not associated with said stopping device.
- 3. (previously presented) The programmable unit according to claim 2, wherein said other components which can be stopped by said stopping device include units which are connected to and cooperate with said program operation unit and said further program operation unit.
- 4. (previously presented) The programmable unit according to claim 3, wherein said units are stopped by said stopping device later in time than said program operation unit and said further program operation unit.
- 5. (previously presented) The programmable unit according to claim 4, including at least one bus connected between said other components.

T-992 P04/15 U-978

- (previously presented) The programmable unit according to claim 5, including bus interfaces and each of said bus interfaces is connected to one of said program operation unit and said further program operation unit and to said bus, said program operation unit and said further program operation unit function as bus masters, said units are stopped only when said bus masters and said bus interfaces have no more data to output and/or are no longer waiting for already requested data or data that is still to be requested.
- (original) The programmable unit according to claim 5, wherein said

bus includes a first bus part, a second bus part and a bus bridge connecting said first bus part to said second bus part, said units are stopped only when said bus bridge has no more data to pass on.

- (previously presented) The programmable unit according to claim 1, wherein after a stopped state of components of the programmable unit which have been stopped is cancelled, said units recommence operation before said program operation unit and said further program operation unit recommence operation.
- The programmable unit according to claim 6, (original) wherein said units function as bus slaves and after a stopped

state of components which have been stopped is cancelled, only said bus slaves recommencing operation, and said bus masters recommencing operation only after said bus slaves have recommenced operation.

- 10. (original) The programmable unit according to claim 1, wherein said stopping device is an on-chip debug support module..
- 11. (currently amended) A programmable unit, comprising:
- at least one program operation unit for running a program;
- a stopping device connected to said program operation unit, said stopping device stopping the running of the program by said program operation unit; and

peripherals connected to said stopping device, said stopping device also—issuing a stop command directly to said peripherals causing said peripherals to be stopped, in addition to stopping said program operation unit with which said stopping device is associated.

12. (previously presented) The programmable unit according to claim 11, wherein said peripherals are stopped by said

stopping device later in time than said program operation unit.

- 13. (previously presented) The programmable unit according to claim 12, including at least one bus connected between said peripherals.
- 14. (previously presented) The programmable unit according to claim 13, including a bus interface connected to said program operation unit and to said bus, said program operation unit functioning as a bus master, said peripherals being stopped only when said bus master and said bus interface have no more data to output and/or are no longer waiting for already requested data or data that is still to be requested.
- 15. (previously presented) The programmable unit according to claim 14, wherein said bus includes a first bus part, a second bus part and a bus bridge connecting said first bus part to said second bus part, said units are stopped only when said bus bridge has no more data to pass on.
- 16. (previously presented) The programmable unit according to claim 11, wherein after a stopped state of peripherals of the programmable unit which have been stopped is cancelled,

said units recommence operation before said program operation unit recommences operation.

(previously presented) The programmable unit according to claim 11, wherein said stopping device is an on-chip debug support module.